



ARX

ARX Range Bufferzone approved

size :

- 02
- 025
- 03



ISO colour code

Flat fan nozzle with air injection :

- ▶ Drift reduction.
- ▶ Buffer zone approved for 02, 025, 03 (yellow, lilac, blue).
- ▶ For all applications requiring an important drift reduction.
- ▶ Application : advised with systemic chemicals.
- ▶ Kwix cap : ¼ quick fit.
- ▶ Inserts : 2 ceramic inserts.

nozai

A broad field of applications

- Kwix cap : ¼ quick fit
- Ceramic flow calibration insert
- Air suction orifice
- Venturi : air suction zone
- Mixing chamber
- Ceramic spraying insert



350 to 710 μ



	Bar	ℓ / min	Flow ℓ / ha according to the forward speed and with 0,50m nozzle spacing							
			5 km/h	6 km/h	7 km/h	8 km/h	9 km/h	10 km/h	11 km/h	12 km/h
ARX 015 green	5,0	0,75	180	150	129	113	100	90	82	75
	6,0	0,84	202	168	144	126	112	101	92	84
	7,0	0,92	221	184	158	138	123	110	100	92
ARX 02 yellow	5,0	1,01	242	202	173	152	135	121	110	101
	6,0	1,11	266	222	190	167	148	133	121	111
	7,0	1,22	293	244	209	183	163	146	133	122
ARX 025 lilac	5,0	1,28	307	256	219	192	171	154	140	128
	6,0	1,40	336	280	240	210	187	168	153	140
	7,0	1,53	367	306	262	230	204	184	167	153
ARX 03 blue	5,0	1,53	367	306	262	230	204	184	167	153
	6,0	1,64	394	328	281	246	219	197	179	164
	7,0	1,83	439	366	314	275	244	220	200	183

Your local dealer

nozal

A broad field of applications

rue de l'Industrie - 51200 EPERNAY - FRANCE

www.nozal.fr